

Product Description

The Scotch-Brite™ Black Floor Pad is a premium-quality floor maintenance scrubbing and stripping pad. It is made of high-quality synthetic fiber in an open-textured non-woven construction. Abrasive particles are dispersed throughout and bonded with a durable adhesive. Each floor pad has a pre-cut center hole. Designed to strip floor finish from floors prior to refinishing. For use on standard, low-speed automatic scrubbers and rotary floor machines (150 - 250 RPM)

Special Features

- Very aggressive mineral particles for effective removal of floor finishes and dirt.
- Blend of fibers to increase friction on floors and to remove black marks and stains.
- Easy washing of pads after use.
- Consistent performance.
- Durable pad at work.

Applications

The Scotch-Brite™ Black Floor Pad is used with stripping solutions and standard low-speed rotary floor machines (swing machines or scrubber dryers) for wet stripping floor finishes on hard floors. It can also be used for heavy-duty cleaning on concrete and industrial floors.

Packaging

Each carton shall be labelled to identify the contents by product name, size, quantity, and manufacturer.

Standard Sizes

Circular discs are available in a variety of common sizes.

Directions for Use

1. Install under the machine pad holder
2. Apply the stripping solution on the floor with a mop
3. Allow to stand for the amount of time following stripping chemical instructions
4. Strip the floor with a floor machine, adding water to keep the floor wet during the process
5. Pick up dirty solution, rinse the stripped floor with clear water and clean mop, and let the floor dry before recoating or re-opening to traffic
6. Remove the pad and wash it

Floor Pad Maintenance

1. Remove the pad from the machine after each use
2. Wash and rinse under tap water or spray water, or keep pads soaked in diluted stripping solution to dissolve caked-on finish (avoid dirty pads from drying before washing)
3. Rinse and hang up to dry

Note: Do not machine wash!

Product Characteristics

The values displayed are the results of illustrative lab test measures and shall not be considered as a commitment from 3M.

Color:	Black
Printing:	Black "Scotch-Brite™" logo
Thickness:	26 mm
Center hole:	Pre-cut at 85 mm
Weight:	2500 g/m ²
Fibre type:	Nylon
Durability:	5000 sqm at 150 RPM in standard use with appropriate maintenance
Aggressiveness:	3.2 g (Schiefer Value)

Storage Conditions and Shelf Life

Storage conditions: +4°C to +40°C, out of sunlight, original container in a clean and dry indoor area.

Health and Safety

When handling any chemical products, read the manufacturer's container labels and the Safety Data Sheets (SDS) for important health, safety, and environmental information.

[Follow the link to obtain SDS sheets for 3M products on 3M.com/SDS.](https://www.3m.com/SDS)

[Follow the link to obtain information about substances of very high concern \(SVHC\).](#)

IMPORTANT!

- When using any equipment, always follow the manufacturer's instructions for safe operation.
- This floor pad is for professional or industrial use only.



DANGER

To reduce the risks associated with inhalation of or exposure to contaminants:
DO NOT use this product on any asbestos-containing material.



WARNING

To reduce the risks associated with inhalation of or exposure to contaminants:

- Ensure this product is used in the recommended applications with the suggested equipment.
- Do not allow this product to be used by untrained operators.
- Always follow standard safety practices, including wearing appropriate protective apparel and eye protection, while using this product.

To reduce the risks associated with environmental contamination:

- Dispose of waste and slurries generated from wet polishing in accordance with all applicable local and government regulations.



CAUTION

The product is intended for wet floor maintenance processes only. DO NOT use this product in any dry application.

Warranty Information

Limited Remedy

This bulletin provides technical information only.

3M recommended product end uses are listed in each 3M product bulletin. End uses not listed in the applicable 3M Product Bulletins are typically not eligible for 3M Warranties. For non-recommended and/or non-warranted end uses or applications, users must test and approve the end uses or applications, assume any associated risks, and acknowledge that 3M has no liability for such end uses or applications. Please contact your 3M representative with any questions about applications, end uses, and warranties.

Limitations of liability

All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.

3M and Scotch-Brite are trademarks of 3M. All other trademarks are the property of their respective owners.

3M United Kingdom PLC

Commercial Branding and Transportation
Cain Road
Bracknell, RG12 8HT
UK