

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : UB10
Product code : 991
Type of product : Detergent
Product group : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Industrial use, Professional use
Industrial/Professional use spec : Industrial
For professional use only
Use of the substance/mixture : Degreaser

1.3. Details of the supplier of the safety data sheet

Manufacturer

Christeyns Professional Hygiene UK Ltd
Clover House
Macclesfield Road
SK23 7DQ Whaley Bridge, Derbyshire
United Kingdom
T 01663 733114, F 01663 733115
info.cph.uk@christeyns.com, www.christeyns-ph.co.uk

Supplier

Christeyns NV
Afrikalaan 182
9000 GENT
Belgium
T +32 (0)9/ 223 38 71, F +32 (0)9/ 233 03 44
info@christeyns.be, www.christeyns.com

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 1 H314
Serious eye damage/eye irritation, Category 1 H318
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

Signal word (CLP) :

Danger

Contains :

sodium hydroxide; Isotridecanol, ethoxylated; Poly(oxy-1,2-ethanediyl), .alpha.-(2-propylheptyl)-.omega.-hydroxy- ; 2-aminoethanol; ethanalamine

Hazard statements (CLP) :

H314 - Causes severe skin burns and eye damage.

Precautionary statements (CLP) :

P102 - Keep out of reach of children.
P260 - Do not breathe spray.
P280 - Wear protective gloves, eye protection.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P315 - Get immediate medical advice/attention.

UB10

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362 - Take off contaminated clothing.

2.3. Other hazards

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Isotridecanol, ethoxylated	CAS-no: 69011-36-5 REACH-no: polymer	5 – 10	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Dam. 1, H318
BUTOXYETHANOL substance with national workplace exposure limit(s) (BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PT, RO, SE, SI, SK, AL, IS, NO, RS, CH); substance with a Community workplace exposure limit	CAS-no: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0 REACH-no: 01-2119475108-36	3 – 5	Acute Tox. 4 (Oral), H302 (ATE=1200 mg/kg bodyweight) Acute Tox. 3 (Inhalation:vapour), H331 (ATE=3 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319
3-butoxypropan-2-ol; propylene glycol monobutyl ether substance with national workplace exposure limit(s) (CZ)	CAS-no: 5131-66-8 EC-No.: 225-878-4 EC Index-No.: 603-052-00-8	3 – 5	Eye Irrit. 2, H319 Skin Irrit. 2, H315
β -Alanine, N-(2-carboxyethyl)-, N-coco alkyl derivs., disodium salts	CAS-no: 90170-43-7 EC-No.: 290-476-8 REACH-no: 01-2119976233-35	3 – 5	Eye Irrit. 2, H319
Poly(oxy-1,2-ethanediyl), .alpha.-(2-propylheptyl)-.omega.-hydroxy-	CAS-no: 160875-66-1	1 – 3	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Dam. 1, H318
2-aminoethanol; ethanolamine substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-no: 141-43-5 EC-No.: 205-483-3 EC Index-No.: 603-030-00-8	1 – 3	Acute Tox. 4 (Oral), H302 (ATE=1089 mg/kg bodyweight) Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Corr. 1B, H314 STOT SE 3, H335 Aquatic Chronic 3, H412
sodium hydroxide substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LV, PL, PT, RO, SE, SK, IS, NO, MK, CH, TR)	CAS-no: 1310-73-2 EC-No.: 215-185-5 EC Index-No.: 011-002-00-6 REACH-no: 01-2119457892-27	1 – 3	Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318
Sodium xylenesulphonate	CAS-no: 1300-72-7 EC-No.: 215-090-9 REACH-no: 01-2119513350-56	1 – 3	Eye Irrit. 2, H319

UB10

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
2-aminoethanol; ethanolamine	CAS-no: 141-43-5 EC-No.: 205-483-3 EC Index-No.: 603-030-00-8	(5 ≤ C ≤ 100) STOT SE 3; H335
sodium hydroxide	CAS-no: 1310-73-2 EC-No.: 215-185-5 EC Index-No.: 011-002-00-6 REACH-no: 01-2119457892-27	(0.5 ≤ C < 2) Eye Irrit. 2; H319 (0.5 ≤ C < 2) Skin Irrit. 2; H315 (2 ≤ C < 5) Skin Corr. 1B; H314 (5 ≤ C ≤ 100) Skin Corr. 1A; H314

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
Inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
Skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
Eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
Ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Acute effects skin	: May cause burns. Causes skin irritation.
Acute effects eyes	: Causes serious eye damage.
Acute effects oral route	: Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

UB10

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep container tightly closed.
Incompatible products	: Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.
Packaging materials	: polyethylene. stainless steel.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

sodium hydroxide (1310-73-2)	
Ireland - Occupational Exposure Limits	
Local name	Sodium hydroxide
OEL STEL	2 mg/m ³
Remark	Advisory OELV (Advisory Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2024
United Kingdom - Occupational Exposure Limits	
Local name	Sodium hydroxide
WEL STEL (OEL STEL)	2 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
BUTOXYETHANOL (111-76-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Butoxyethanol
IOEL TWA	98 mg/m ³
	20 ppm
IOEL STEL	246 mg/m ³
	50 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE) [Ethylene glycol monobutyl ether]
OEL TWA	98 mg/m ³
	20 ppm
OEL STEL	246 mg/m ³
	50 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values), Skin (Substances which have the capacity to penetrate intact skin when they come in contact with it and be absorbed into the body. A substantial contribution to the total body burden via dermal exposure is possible)
Regulatory reference	Chemical Agents Code of Practice 2024
United Kingdom - Occupational Exposure Limits	
Local name	2-Butoxyethanol
WEL TWA (OEL TWA)	123 mg/m ³
	25 ppm
WEL STEL (OEL STEL)	246 mg/m ³
	50 ppm

UB10

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTOXYETHANOL (111-76-2)	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	2-Butoxyethanol
BMGV	240 mmol/mol Creatinine Parameter: butoxyacetic acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
2-aminoethanol; ethanolamine (141-43-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Aminoethanol
IOEL TWA	2.5 mg/m ³
	1 ppm
IOEL STEL	7.6 mg/m ³
	3 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Ireland - Occupational Exposure Limits	
Local name	2-Aminoethanol [Ethanolamine]
OEL TWA	2.5 mg/m ³
	1 ppm
OEL STEL	7.6 mg/m ³
	3 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values), Skin (Substances which have the capacity to penetrate intact skin when they come in contact with it and be absorbed into the body. A substantial contribution to the total body burden via dermal exposure is possible)
Regulatory reference	Chemical Agents Code of Practice 2024
United Kingdom - Occupational Exposure Limits	
Local name	2-Aminoethanol
WEL TWA (OEL TWA)	2.5 mg/m ³
	1 ppm
WEL STEL (OEL STEL)	7.6 mg/m ³
	3 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

UB10

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Wear eye protection. Chemical goggles or safety glasses

Skin protection

Hand protection:

Wear protective gloves

Other skin protection

Materials for protective clothing:

Wear protective clothing

Environmental exposure controls

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Red.
Physical state/form	: Liquid.
Odour	: Characteristic.
Odour threshold	: Not available
Melting point/range	: 0 °C
Freezing point	: Not determined as it is not relevant for the characterization of the product
Boiling point/Boiling range	: 100 °C
Flammability	: Not determined as it is not relevant for the characterization of the product Non flammable.
Lower explosion limit	: Constituents do not contain chemical groups associated with explosivity
Upper explosion limit	: Constituents do not contain chemical groups associated with explosivity
Flash point	: Not determined as it is not relevant for the characterization of the product
Autoignition temperature	: Determination of the auto-ignition temperature is only relevant for pyrophoric liquids, however the mixture is not a pyrophoric liquid so the test is not required.
Decomposition temperature	: Only applies to self-reactive substances and mixtures, organic peroxides, and other substances and mixtures that may decompose.
pH	: 13 – 14
Viscosity, kinematic	: Not available
Viscosity, dynamic	: < 20 cP at 20 °C
Solubility	: Soluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1.04 g/cm ³
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

UB10

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

BUTOXYETHANOL (111-76-2)	
LD50 oral rat	1200 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat [ppm]	4500
LC50 Inhalation - Rat (Dust/Mist)	1.5 mg/l
LC50 Inhalation - Rat (Vapours)	3 mg/l/4h

3-butoxypropan-2-ol; propylene glycol monobutyl ether (5131-66-8)	
LD50 oral rat	5660 mg/kg Source: NLM;HSDB, TOMES;LOLI;
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	3100 mg/kg Source: NLM;chemIDplus, TOMES;LOLI;
LC50 Inhalation - Rat (Vapours)	> 3.5 mg/l/4h

Poly(oxy-1,2-ethanediyl), .alpha.-(2-propylheptyl)-.omega.-hydroxy- (160875-66-1)	
LD50 oral	500 mg/kg

2-aminoethanol; ethanolamine (141-43-5)	
LD50 oral rat	1089 mg/kg Source: OECD SIDS
LD50 oral	1515 mg/kg bodyweight
LD50 dermal rabbit	2504 mg/kg Source: OECD SIDS
LD50 dermal	2504 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	136 mg/l
LC50 Inhalation - Rat (Vapours)	> 1487 mg/l Source: ECHA

Sodium xylenesulphonate (1300-72-7)	
LD50 oral	> 7000 mg/kg bodyweight
LD50 dermal	> 2000 mg/kg bodyweight

Skin corrosion/irritation : Causes severe skin burns.
pH: 13 – 14

Additional information : Based on available data, the classification criteria are not met

2-aminoethanol; ethanolamine (141-43-5)	
pH	≈ 12

Serious eye damage/irritation : Causes serious eye damage.
pH: 13 – 14

Additional information : Based on available data, the classification criteria are not met

UB10

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-aminoethanol; ethanolamine (141-43-5)	
pH	≈ 12

Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met

BUTOXYETHANOL (111-76-2)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met

2-aminoethanol; ethanolamine (141-43-5)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met

β-Alanine, N-(2-carboxyethyl)-, N-coco alkyl derivs., disodium salts (90170-43-7)	
--	--

LOAEL (oral, rat, 90 days)	160 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 90 days)	43 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

3-butoxypropan-2-ol; propylene glycol monobutyl ether (5131-66-8)	
--	--

LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	350 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	880 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met

2-aminoethanol; ethanolamine (141-43-5)	
Viscosity, kinematic	18.578 mm ² /s

11.2. Information on other hazards

Other information

Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met
---	--

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

sodium hydroxide (1310-73-2)	
LC50 - Fish [1]	> 35 mg/l
EC50 - Crustacea [1]	40.4 mg/l (Ceriodaphnia)
EC50 - Other aquatic organisms [1]	> 33 mg/l waterflea

UB10

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

β-Alanine, N-(2-carboxyethyl)-, N-coco alkyl derivs., disodium salts (90170-43-7)	
LC50 - Fish [1]	≈ 4.2 mg/l Test organisms (species): <i>Oncorhynchus mykiss</i> (previous name: <i>Salmo gairdneri</i>)
EC50 - Crustacea [1]	≈ 29 mg/l Test organisms (species): <i>Daphnia magna</i>
EC50 72h - Algae [1]	≈ 5.5 mg/l Test organisms (species): <i>Chlorella vulgaris</i>
EC50 72h - Algae [2]	≈ 9.4 mg/l Test organisms (species): <i>Chlorella vulgaris</i>
NOEC (chronic)	≈ 10 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
BUTOXYETHANOL (111-76-2)	
LC50 - Fish [1]	1474 mg/l
EC50 - Crustacea [1]	1550 mg/l <i>Daphnia magna</i>
EC50 72h - Algae [1]	1840 mg/l
NOEC (chronic)	100 mg/l
NOEC chronic crustacea	100 mg/l <i>Daphnia magna</i>
NOEC chronic algae	130 mg/l
3-butoxypropan-2-ol; propylene glycol monobutyl ether (5131-66-8)	
LC50 - Fish [1]	560 – 1000 mg/l Test organisms (species): <i>Poecilia reticulata</i>
EC50 - Crustacea [1]	> 1000 mg/l Test organisms (species): <i>Daphnia magna</i>
EC50 96h - Algae [1]	> 1000 mg/l Test organisms (species): <i>Pseudokirchneriella subcapitata</i> (previous names: <i>Raphidocelis subcapitata</i> , <i>Selenastrum capricornutum</i>)
2-aminoethanol; ethanolamine (141-43-5)	
LC50 - Fish [1]	349 mg/l
LC50 - Fish [2]	170 mg/l <i>Carassius auratus</i> (goldfish)
EC50 - Crustacea [1]	32.6 mg/l
EC50 - Other aquatic organisms [1]	65 mg/l waterflea
EC50 - Other aquatic organisms [2]	2.5 mg/l
EC50 72h - Algae [1]	22 mg/l <i>Scenedesmus subspicatus</i>
ErC50 algae	2.1 mg/l Source: ECHA
NOEC chronic fish	1.2 mg/l <i>Oryzias latipes</i> (Orange-red killifish); 30 d
NOEC chronic crustacea	0.85 mg/l <i>Daphnia magna</i> , 21 days
Sodium xylenesulphonate (1300-72-7)	
EC50 - Other aquatic organisms [1]	> 1020 mg/l waterflea
12.2. Persistence and degradability	
UB10	
Persistence and degradability	Biodegradable. The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.
sodium hydroxide (1310-73-2)	
Persistence and degradability	The methods for determining biodegradability are not applicable to inorganic substances.
β-Alanine, N-(2-carboxyethyl)-, N-coco alkyl derivs., disodium salts (90170-43-7)	
Persistence and degradability	Rapidly degradable
BUTOXYETHANOL (111-76-2)	
Persistence and degradability	Biodegradable.
3-butoxypropan-2-ol; propylene glycol monobutyl ether (5131-66-8)	
Persistence and degradability	Rapidly degradable

UB10

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3-butoxypropan-2-ol; propylene glycol monobutyl ether (5131-66-8)	
Biodegradation	90 % 28 days; OECD 301 E
2-aminoethanol; ethanolamine (141-43-5)	
Biochemical oxygen demand (BOD)	8 g O ₂ /g substance Incubation time: 5 days
Biodegradation	> 90 % 21 days, OECD 301A
Sodium xylenesulphonate (1300-72-7)	
Persistence and degradability	Rapidly degradable
12.3. Bioaccumulative potential	
UB10	
Bioaccumulative potential	No bioaccumulation.
sodium hydroxide (1310-73-2)	
Log Pow	-3.88
Bioaccumulative potential	No bioaccumulation.
BUTOXYETHANOL (111-76-2)	
Log Pow	0.81
3-butoxypropan-2-ol; propylene glycol monobutyl ether (5131-66-8)	
Partition coefficient n-octanol/water (Log Kow)	1.2
2-aminoethanol; ethanolamine (141-43-5)	
Log Pow	-1.31
Partition coefficient n-octanol/water (Log Kow)	-1.91
Sodium xylenesulphonate (1300-72-7)	
Log Pow	-3.12
12.4. Mobility in soil	
3-butoxypropan-2-ol; propylene glycol monobutyl ether (5131-66-8)	
Mobility in soil	9.228
12.5. Results of PBT and vPvB assessment	
UB10	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
12.6. Endocrine disrupting properties	
No additional information available	
12.7. Other adverse effects	
UB10	
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Waste / unused products	: Avoid release to the environment.
HP Code	: HP8 - "Corrosive:" waste which on application can cause skin corrosion.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number or ID number		
Not regulated for transport		
14.2. UN proper shipping name		
Not regulated	Not regulated	Not regulated

UB10

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA
14.3. Transport hazard class(es)		
Not regulated	Not regulated	Not regulated
14.4. Packing group		
Not regulated	Not regulated	Not regulated
14.5. Environmental hazards		
Not regulated	Not regulated	Not regulated
No supplementary information available		

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Detergent Regulation (EC 648/2004)

Labelling of contents	
Component	%
non-ionic surfactants	5-15%
amphoteric surfactants	<5%

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

UB10

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Data sources

: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information

: None.

Full text of H- and EUH-statements:

Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Skin Corr. 1	H314	On basis of test data
Eye Dam. 1	H318	On basis of test data

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.